

FLowsERVE

Vogt Valves

Vogt Valves

*The Connection Bulletin for
Forged Steel
Gate, Globe & Check Valves*

CB 06

Forged Steel GATE, GLOBE & CHECK VALVES



HEAVY DUTY VALVES CONFORMING TO API-600 WALL THICKNESS






Vogt heavy duty **flanged, threaded and socket weld end valves are made from** rugged, finegrained steel forgings.

These valves are manufactured in a wide variety of constructions, types and ASME pressure classes. They are available with renewable seats, as well as full ports or conventional ports.

This group of Gate, Globe and Check Valves meet **API-600 wall thickness** requirements.

Inherent in this requirement is a greater **corrosion allowance**. Where applicable, the valves meet other recognized standards such as ASME B16.5, B16.10, B16.11 and B16.34.

Forged Steel GATE, GLOBE & CHECK VALVES

DESCRIPTION	PRESSURE/SIZE DESIGNATION	MATERIAL		SERIES NUMBER	
		Body/Bonnet	Trim	Threaded	Socket Weld
 <p>BOLTED BONNET Outside Screw and Yoke Gate Valve</p>	Class 800 Full Port 1975 psi @ 100°F Sizes 1/2 - 3 ▲	A105	13% Cr.★	11103	SW 11103
	Class 1500 Full Port 3705 psi @ 100°F Sizes 1/2 - 2	A105	13% Cr.★	1033	SW 1033
		A105	13% Cr.★	1043	SW 1043
 <p>BOLTED BONNET Outside Screw and Yoke Gate Valve</p>	Class 600 Full Port 1480 psi @ 100°F Sizes 1/2 - 3 ▲	A105	13% Cr.★	11403 (1/4" Raised Faces)	
	Class 1500 Full Port 3705 psi @ 100°F Flanged 1/4" R.F. and Flanged R.J. Faces Sizes 1/2 - 2	A105	13% Cr.★	11603 (1/4" Raised Faces)	
		A105	13% Cr.★	11683 (Ring Joint Faces)	
 <p>BOLTED BONNET Outside Screw and Yoke Globe Valve</p>	Class 800 1975 psi @ 100°F Sizes 1/2 - 3	A105	13% Cr.	10103	SW 10103
	Class 1500 Full Port 3705 psi @ 100°F Sizes 1/2 - 2	A105	13% Cr.	1023	SW 1023
		A105	13% Cr.	1003	SW 1003
 <p>BOLTED BONNET Outside Screw and Yoke Globe Valve</p>	Class 600 1480 psi @ 100°F Flanged 1/4" R.F. Sizes 1/2 - 3	A105	13% Cr.	10403 (1/4" Raised Faces)	
	Class 1500 Full Port 3705 psi @ 100°F Flanged 1/4" R.F. and Flanged R.J. Faces Sizes 1/2 - 2	A105	13% Cr.	10603 (1/4" Raised Faces)	
		A105	13% Cr.	10683 (Ring Joint Faces)	
 <p>BOLTED BONNET Horizontal Type Swing Type Check Valve</p>	Class 800 1975 psi @ 100°F Sizes 1/2 - 2	A105	13% Cr.	4835	SW 4835

Flanged valve flanges conform to ASME Standard BI 6.5 and end-to-end dimensions conform to ASME Standard BI 6.1 O.

★ Seats are hard faced.

▲ Full Port except Sizes 2-1/2 & 3.

Vogt Heavy Duty valves are available with a wide variety of special trims, packing materials and flange facings.

For complete specifications on all Edward Vogt valves refer to the Vogt Catalog.



Vogt Valves

1511 Jefferson Street
Sulphur Springs, TX 75482

US Sales Offices

Phone: 903-885-3151
Fax: 903-439-3386

Toll-Free Telephone Service

1-800-225-6989

Visit Our Website

www.flowserve.com

After Hours Customer Service

1-800-543-3927

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can (and often does) provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Operation Maintenance (IOM) instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

For more information about Flowserve Corporation, contact www.flowserve.com or call USA 1-800-225-6989.

FLOWSERVE CORPORATION

FLOW CONTROL DIVISION

Vogt Valves

1511 Jefferson Street
Sulphur Springs, TX 75482
Phone: 903-885-3151
Facsimile: 903-439-3386